



Lubricant for **transmissions with oil immersed disc brakes** and hydraulic systems used in agricultural tractors and Public Works or handling equipment.

APPLICATIONS

- ELF TRACTELF NG has been especially developed for **transmissions with wet brakes** requiring an **API GL-4 lubricant** with a 10W-30 or 80W viscosity grade, in both Off-Road and On-Road vehicles.
- This lubricant is also perfectly adapted to **automatic transmissions, torque converters and hydrostatic transmissions** and more generally to any transmissions requiring an **UTTO** (Universal Tractor Transmissions Oil).
- ELF TRACTELF NG is approved for multiple **ZF** transmissions, including CVT types, and is recommended for **KUBOTA** transmissions requiring the "**UDT**" approval. This product is also designed for applications such as **hydraulic circuits, power-steerings and power-take-offs (PTO) with wet clutches**.

SPECIFICATIONS AND APPROVALS

International specifications	API GL-4
Manufacturers' approvals	<ul style="list-style-type: none"> ✓ ZF TE-ML 03E/05F/06D/06K/06N/06R/17E/21F ✓ VALTRA G2-08 ✓ VOLVO CE WB 101
Suitable when the following specifications/products are recommended	<ul style="list-style-type: none"> ✓ MASSEY FERGUSON CMS M 1145/M 1143 ✓ JOHN DEERE JDM J20C ✓ CLAAS / RENAULT AGRICULTURE ✓ FORD FNHA 2C 201.00 / M2C 134-D ✓ Mc CORMICK HTX
Recommended for	<ul style="list-style-type: none"> ✓ CASE MS1206/MS1207/MS1209 ✓ CNH MAT 3505/3509/3525/3526/3540 ✓ NEW HOLLAND NH 410C/NH 410B ✓ KOMATSU AXO 80 ✓ MASSEY FERGUSON CMS M 1135/M 1141 ✓ KUBOTA UDT ✓ AGCO : ALLIS 821 XL

PERFORMANCES AND CUSTOMER BENEFITS

- ELF TRACTELF NG is adapted to a wide range of agricultural and Public Works equipment and helps to reduce the stock and the number of lubricants.
- This lubricant shows **excellent low temperature performances** (protects friction brakes against sticking) and **high temperature performances** (protects against judder or excessive slip).
- ELF TRACTELF NG has **very good extreme pressure and anti-wear properties** giving optimum protection of gears and hydraulic components.

PHYSICAL AND CHEMICAL CHARACTERISTICS*

ELF TRACTELF NG *		Method	Value
Viscosity at 40°C	mm ² /s	ASTM D445	66
Viscosity at 100°C	mm ² /s	ASTM D445	10.6
Viscosity Index	-	ASTM D2270	150
Pour Point	°C	ASTM D97	-42

* The features mentioned above are average values obtained with some variability in production and do not constitute a specification.